
Model No. 2400LR

Ligature Resistant Flush Wall Mount with Angled Armature Head





- For Use In Behavioral Health Facilities, Hospitals, Correctional Facilities And Any Institution Where It Is Needed To Help Support A Safer Envriontment And Where Safety Is Of The Highest Priority.

FINISHES US28, S1/ALPC, S2/BSPC, S3/BZPC, S4/BSPC, S5/DBPC, Custom Finishes Available

MATERIAL Stainless Steel Base Material

FEATURES

- 9/32" Total Projection From Wall to Door Face
- Tri-Voltage* (12V DC, 24V AC/DC, or 120V AC)
- All-Metal Construction (No Plastic Parts)
- 2-Point Pivot For 360° Door Armature Mobility
  - Improves Door Alignment
  - Reduces Installation Time
- Positive Release Button Alleviates Residual Magnetism
- Standard 1½" Door Armature (Extendable with Six ¼" Rings Included)
- 35 lbs. Holding Force
- Optional Extensions (To Fill Gap Between Magnet and Door) Available without Adapter Piece
- Wall Cover And Door Armature Sloped To Prevent Objects From Being Tied Or Looped Around Them
- Door Armature Head Has 3° Adjustment Built In For Maximum Flexibility For Uneven Wall Conditions
- California State Fire Marshall Listed
- UL/ULC Listed for Smoke Barrier or Labeled Fire Door
- Meets and/or Exceeds ANSI/BHMA Standard A156.16

FASTENERS

- Magnetic Wall: 2) 6-32 x 1" Oval Head Machine Screw
- Magnetic Cover: 2) 6-32 x ¾" S.S. Pin Torx Flat Head Machine Screw
- Door Armature: 2) ¼-20 x 2" S.S. Pin Torx Round Head Machine Screw

OPTIONS

CODE	DESCRIPTION
SEC	Security Fasteners for All Exposed Areas
THICK	Fasteners for 1⅜" or 2¼" Thick Door (Please Specify)

BABA BUILD AMERICA, BUY AMERICA COMPLIANT · BHMA CERTIFIED · ANSI American National Standards Institute · UL

abhmfg.com

Made in ITASCA, USA & Family-Owned
Our Parts Are Made of MORE.

Architectural Builders Hardware Manufacturing Inc.
740 Hilltop Drive, Itasca, IL 60143
TEL 630.875.9900 FAX 800.932.9224

Don't be shy. If you have any ?s call on us.