
ARCHITECTURAL BUILDERS HARDWARE

Model No. 2400LS

Flush Wall Mount with Extreme Low Profile Armature





FINISHES US28, US32, US32D, S1/ALPC, S2/BSPC, S3/BZPC, S4/BSPC, S5/DBPC, Custom Finishes Available

MATERIAL Stainless Steel Base Material

FEATURES

- ⅝" Total Projection From Wall to Door Face
- Tri-Voltage* (12V DC, 24V AC/DC, or 120V AC)
- All-Metal Construction (No Plastic Parts)
- California State Fire Marshall Listed
- 2-Point Pivot For 360° Door Armature Mobility
  - Improves Door Alignment
  - Reduces Installation Time
- Positive Release Button Alleviates Residual Magnetism
- 35 lbs. Holding Force
- Extensions (To Fill Gap Between Magnet and Door) Available without Adapter Piece
- Outlet Box Required (Not Provided)
- Average Weight Per Unit: 2 Lbs.
- UL/ULC Listed for Smoke Barrier or Labeled Fire Door
- Meets and/or Exceeds ANSI/BHMA Standard A156.16

FASTENERS

- Magnetic Wall: 2) 6-32 x 1" Oval Head Machine Screw
- Magnetic Cover: 2) 6-32 x 1" Flat Head Machine Screw
- Door Armature:
  1) 10-32 x 1" Pan Head Machine Screw
  1) 10-32 x 1¼" SNB -OR- 10 x 1" Flat Head SMS

OPTIONS

CODE	DESCRIPTION
SEC	Security Fasteners for All Exposed Areas
THICK	Fasteners for 1⅜" or 2¼" Thick Door (Please Specify)

BABA BUILD AMERICA, BUY AMERICA COMPLIANT · BHMA CERTIFIED · ANSI American National Standards Institute · UL

abhmfg.com

Made in ITASCA, USA & Family-Owned
Our Parts Are Made of MORE.

Architectural Builders Hardware Manufacturing Inc.
740 Hilltop Drive, Itasca, IL 60143
TEL 630.875.9900 FAX 800.932.9224

Don't be shy. If you have any ?s call on us.