OVERHEAD HOLDERS & STOPS / SURFACE MOUNTED HEAVY DUTY

Model No. 9000, N9000

Heavy Duty, Surface Mount



MODELS

MODEL NO.			FRAME OPENING SIZE (NOMINAL)	
HOLD OPEN	STOP	FRICTION	BUTT HINGES OR OFFSET PIVOTS	CENTER HUNG
9018	9028	9038	24" - 27 5/16"	26" - 29 15/16"
9011	9021	9031	28" - 29 5/16"	30" - 33 15/16"
9012	9022	9032	30" - 31 5/16"	34" - 35 15/16"
9013	9023	9033	32" - 35 5/16"	36" - 38 15/16"
9014	9024	9034	36" - 39 5/16"	39" - 40 15/16"
9015	9025	9035	41" - 44 15/16"	41" - 44 15/16"
9016	9026	9036	42" - 43 5/16"	45" - 46 15/16"
9017	9027	9037	44" - 54"	47" - 56"

N MODELS

MODEL NO.			FRAME OPENING SIZE (NOMINAL)	
HOLD OPEN	STOP	FRICTION	BUTT HINGES OR OFFSET PIVOTS	CENTER HUNG
N9018	N9028	N9038	24" - 27 5/16"	26" - 29 15/16"
N9011	N9021	N9031	28" - 29 5/16"	30" - 33 15/16"
N9012	N9022	N9032	30" - 31 5/16"	34" - 35 15/16"
N9013	N9023	N9033	32" - 35 5/16"	36" - 38 15/16"
N9014	N9024	N9034	36" - 39 5/16"	39" - 40 15/16"
N9015	N9025	N9035	41" - 44 15/16"	41" - 44 15/16"
N9016	N9026	N9036	42" - 43 5/16"	45" - 46 15/16"
N9017	N9027	N9037	44" - 54"	47" - 56"

N Models - All Stainless Steel Material

FINISHES US3, US4, US9, US10, US10B, US26, US32, US32D, S1/ALPC, S2/BSPC, S3/BZPC, S4/BSPC, S5/DBPC, S8/WSPC,
Custom Finishes Available

MATERIAL Stainless Steel Standard Base Material

FEATURES

- N - All Stainless Steel Components
- Single Acting Doors Only
- Standard Fasteners Supplied With Sex Bolts For 1¾" To 2¼" Thick Door (See Options For Other Door Thickness)
- No Plastic Part
- Non-Handed
- Interior Or Exterior Use On Frequent Traffic And Heavy Weight Doors
- Standard Installation From 85˚ To 110˚ Of Opening (5˚ Increments)
- Shock Absorbing Spring (3˚ - 5˚ Cushion Before Dead Stop)
- Average Weight Per Unit: 5 lbs.
- Available In Most Standard BHMA Finishes - Done In-House
- Meets Or Exceeds BHMA Standard 156.8
- Classified By UL As Miscellaneous Fire Door Accessory For Use On Wood Fire Doors Rated Up To 90 Minutes + Metal Fire Rated Doors Up to 3 hours

FASTENERS

- Jamb:

4) #14 x 1 1/2" Flat Head Wood Screw
4) 1 1/4" - 20 x 3/4" Flat Head Machine Screw

- Door:

2) #18 x 2 1/2" Flat Head Wood Screw
2) 5/16" - 18 x 1 1/2" Flat Head Machine Screw

BABA BUILD AMERICA, BUY AMERICA COMPLIANT BHMA CERTIFIED UL

abhmfg.com

Made in ITASCA, USA & Family-Owned
Our Parts Are Made of MORE.

Architectural Builders Hardware Manufacturing Inc.
740 Hilltop Drive, Itasca, IL 60143
TEL 630.875.9900 FAX 800.932.9224

Don't be shy. If you have any ?s call on us.

OVERHEAD HOLDERS & STOPS / SURFACE MOUNTED HEAVY DUTY

Model No. 9000, N9000

Options

CODE	DESCRIPTION
N	All Stainless Stee Material
CL	For Use with Cam Lift Hinges (½" Lift Maximum)
HC	Hold-Closed Option (4020, 1020, 4420, 9020 Stop Function Only)
LL-Surface	Lead-Lined (Thru-Bolts for Surface Model)
LS	Less Spring (Stop Function Only)
SEC	Security Fasteners
T	Threaded Pivot Screw & Nylon Washer in Lieu of Standard Jamb Bracket
THICK	Special Door Thickness

Accessories

CODE	DESCRIPTION
90541	Angle Jamb Brackets for 8000, 9000 & 9000A Series (Specify Finish)
9000F-KIT	Friction Conversion Kit for 1000, 1000A, 9000 & 9000A Series
9000HO-KIT	Hold Open Conversion Kit for 9000 & 9000A Series
N9000-KIT	Friction Conversion Kit for N1000, N1000A, N9000 & N9000A Series
N9000HO-KIT	Hold Open Conversion Kit for N9000 & N9000A Series
9000JF	Jamb Bracket Filler/Shim for 1000, 1000SL, 8000 & 9000 Series –¼" Thick (Specify Finish)

BUILD AMERICA, BUY AMERICA COMPLIANT

abhmfg.com

Made in ITASCA, USA & Family-Owned
Our Parts Are Made of MORE.

Architectural Builders Hardware Manufacturing Inc.
740 Hilltop Drive, Itasca, IL 60143
TEL 630.875.9900 FAX 800.932.9224

Don't be shy. If you have any ?s call on us.